


# side kr992723

product name	square side, TC-TEL, grey
<b>general information</b>	
application	recessed luminaire for walls and ceilings
direction of mounting	↕ ↗ ↘
protection class	1
ip classification	40
input voltage	230 V
electric gear	included
<b>measurements</b>	
visible dimensions LxW	326x338 mm
<b>illuminant</b>	
lamptype	TC-TEL
symbol	
fitting	GX24q-3 / GX24q-4
wattage	26 W / 32 W / 42 W
voltage	230 V
type of gear	electronic ballast 230 V
rotation / inclination	none
<b>material and surface</b>	
housing	sheet steel
colour (visible frame / rear)	grey / none
surface treatment	powdercoated / galvanised
<b>glass cover</b>	
included	glass, clear
optional	glass, frosted
The optional frosted glass is used to replace the standard glass.	
<b>cut-out dimensions</b>	
<b>in plasterboard</b>	
cut-out LxW	320x312 mm
required depth	100 mm
possible thickness of panel	8-20 mm
<b>in massive elements</b>	
cut-out LxWxH	395x510x95 mm
Installation in masonry absolutely requires the use of a plasterkit.	
<b>included accessories</b>	
<b>reflectors</b>	
reflector matt	
<b>optional accessories</b>	
<b>glasses, filters and lenses</b>	
kr770710	cover glass frosted
<b>installation boxes</b>	
kr722172	installation box square side
<b>plasterkits</b>	
kr702172	plasterkit square side



**kreon nv**  
Industrieweg Noord 1152  
3660 Opglabbeek  
Belgium  
T +32 89 8197 80  
F +32 89 8197 90  
M mailbox@kreon.com  
www.kreon.com

**remarks**

The orientation of the plasterkit determines the direction of light output.