

Technical drawing of a mechanical part with dimensions and tolerances:

- Top left hole: $\varnothing 32$, $\varnothing 20 \text{ H7}$, $\varnothing 0.05 \text{ A B C}$
- Top middle hole: $2 \times 5 \varnothing 32$, $2 \times 5 \varnothing 17$, $\varnothing 0.1 \text{ C B D}$
- Top right hole: $2 \times 2 \varnothing 32$, $2 \times 2 \varnothing 17$, $\varnothing 0.1 \text{ C B D}$
- Right side hole: 2×45 , $R3$
- Bottom right corner: $Ra 0.8$, 16 , 39.75

Technical drawing of a mechanical part. The part is a rectangular block with a width of 30. It features a top surface with a radius of R5 and a side surface with a radius of R10. A label 'R outill' points to the top surface. A label 'R 10' points to the side surface. A label '30' points to the width of the part.

vue de face

3 × 45°

2x R5

6.0

14.3

200

675 ± 0.1

0.05 A B

0.05 A B

0.05 A

Ra 0.8

Ra 0.8

Prévoir une surépaisseur de 0.5mm pour repise d'usinage avec les pièces 1212 et 1213

Technical drawing of a cross-section of a reinforced concrete slab with a central circular opening. The drawing shows a top view and a side view. The top view is a rectangle with a central circle. The side view shows the profile of the slab and the opening. Dimensions include a total width of 164, a central opening diameter of 20, and a height of 20. A note indicates a slope of 2x 34 x 45. A dimension line at the bottom indicates a distance of 0.2 F from the center to the edge.

Technical drawing of a 2x M16-6H flange. The drawing shows a cross-section of the flange with dimensions: 56 (total height), 44 (height to the top of the flange), and 20 (height of the flange). The flange has two M16-6H holes. The drawing also shows a detail of the flange with a 2x M16-6H hole and a 2x M16-6H hole. The feature control frame indicates a positional tolerance of 0.05 mm for the hole.

[illegible]

Coupe D-D

2X	7	M8 - 6H
Φ 0.1	D	B F

Echelle : 1:2

Technical drawing of a rectangular table with rounded ends, showing top and side views with dimensions in millimeters.

Top View Dimensions:


- Overall width: 606 mm
- Overall length: 608.4 mm
- Width of the central rectangular section: 245 mm
- Radius of the rounded ends: 2 x R30
- Distance from the center of the rounded end to the center of the first leg: 30 mm
- Distance from the center of the rounded end to the center of the second leg: 60 mm
- Distance from the center of the rounded end to the center of the third leg: 335 mm
- Distance from the center of the rounded end to the center of the fourth leg: 387 mm
- Distance from the center of the rounded end to the center of the fifth leg: 427 mm
- Distance from the center of the rounded end to the center of the sixth leg: 477 mm
- Distance from the center of the rounded end to the center of the seventh leg: 502 mm
- Distance from the center of the rounded end to the center of the eighth leg: 552 mm
- Distance from the center of the rounded end to the center of the ninth leg: 602 mm


Side View Dimensions:

- Overall height: 74 mm
- Depth of the table: 335 mm

Other Dimensions:

- Distance from the top edge to the center of the first leg: 80 mm
- Distance from the top edge to the center of the second leg: 40 mm
- Distance from the top edge to the center of the third leg: 40 mm
- Distance from the top edge to the center of the fourth leg: 80 mm
- Distance from the top edge to the center of the fifth leg: 80 mm
- Distance from the top edge to the center of the sixth leg: 80 mm
- Distance from the top edge to the center of the seventh leg: 80 mm
- Distance from the top edge to the center of the eighth leg: 80 mm
- Distance from the top edge to the center of the ninth leg: 80 mm
- Distance from the top edge to the center of the tenth leg: 80 mm
- Distance from the top edge to the center of the eleventh leg: 80 mm
- Distance from the top edge to the center of the twelfth leg: 80 mm

Nbre de pièces: 1	TOLERANCES GENERALES:
Matériau: RAMAX -HH	LONGUEURS = ISO 2768-
Protection: -	ALESAGES = H11
Traitement: -	ARBRES = h11
	USINAGE GENERAL : 
Graver le N° du plan sur une partie	.

A	Création du document		20/08/24	BASHOREAU	NEVEU	LECONTE
no	Modifications		no	Dessiné par	Vérifié par	Approuvé par
<p align="center">SANS MENTION DE PROTECTION</p> <p align="center">ONERA</p> <p align="center">THE FRENCH AEROSPACE LAB</p> <p align="center">BEIR A S1MA</p> <p align="center">SEMELLE</p>						
92500 de la Division Cellule 12000 CHATELAIN			Bureau d'Etudes OSM-IC			
TEL: (33) 01.46.73.40.40			FAX: (33) 01.46.73.41.41			
Ce plan, propriété de l'Onera ne peut être obtenu, reproduit ou communiqué sans son autorisation.						
A0	ECH: 1/2	Maquette au:		CAI/CAI2 CATIA V18R1	S1MA.8.15027.1211	
					Planche: 1/2	

Fichier: W18-15-027 BEIR A 81MA06-CATIA\ETUDE8\1003 - STRUCTURE PRIMAIRE\1200 - STRUCTURE AVANT NON PESEEUP\ans\81MA-8-15027-1211-A_SEMELLE.CATDraw
 Imprimé le : 26/05/2025, 12:40, absence