



160/50

(DE)

- Individuell einstellbarer Code
- Gehärteter Stahlbügel
- Bügelstärke 7,5 mm

(FR)

- Combinaison programmable
- Anse en acier cémenté
- Diamètre anse 7,5 mm

(NL)




- Zelfinstelbare cijfercode
- Gehard stalen beugel
- Beugeldikte 7,5 mm

(IT)

- Combinazione personale
- Arco d'acciaio cementato
- Diametro arco 7,5 mm



a = 50,0 mm
b = 29,0 mm
c = 26,0 mm
d = 7,5 mm



Code

Merkmale - Caractéristiques - Kenmerken - Caratteristiche



- (DE) Individuell einstellbarer Code
- (FR) Combinaison programmable
- (NL) Zelfinstelbare cijfercode
- (IT) Combinazione personale




- (DE) Doppelte Verriegelung
- (FR) Double verrouillage de l'anse
- (NL) Beugel aan beide zijden vergrendeld
- (IT) Entrambe i lati dell'arco sono ben protetti



- (DE) Bügelmaterial aus gehärtetem Stahl
- (FR) Anse en acier cémenté
- (NL) Beugel van gehard staal
- (IT) Anello di trazione fatto con acciaio cementato

Einsatzgebiete - Utilisation - Toepassingsmogelijkheden - Campo d'impiego



©ABUS
D 58292 Wetter
Germany
abus.com



ABUS 160/50 B/DFNLI



331958